

## Bid Document

| Bid Details                                                                  |                                                                                                                                                                                                                                                                  |
|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Bid End Date/Time</b>                                                     | 28-09-2021 15:00:00                                                                                                                                                                                                                                              |
| <b>Bid Opening Date/Time</b>                                                 | 28-09-2021 15:30:00                                                                                                                                                                                                                                              |
| <b>Bid Life Cycle (From Publish Date)</b>                                    | 90 (Days)                                                                                                                                                                                                                                                        |
| <b>Bid Offer Validity (From End Date)</b>                                    | 65 (Days)                                                                                                                                                                                                                                                        |
| <b>Ministry/State Name</b>                                                   | Ministry Of Chemicals And Fertilizers                                                                                                                                                                                                                            |
| <b>Department Name</b>                                                       | Department Of Chemicals And Petrochemicals                                                                                                                                                                                                                       |
| <b>Organisation Name</b>                                                     | Brahmaputra Cracker And Polymer Limited (bcpl) Guwahati Assam                                                                                                                                                                                                    |
| <b>Office Name</b>                                                           | Lepetkata                                                                                                                                                                                                                                                        |
| <b>Total Quantity</b>                                                        | 30                                                                                                                                                                                                                                                               |
| <b>Item Category</b>                                                         | EXTERNAL MICROMETERS , CALIPERS                                                                                                                                                                                                                                  |
| <b>MSE Exemption for Years of Experience and Turnover</b>                    | No                                                                                                                                                                                                                                                               |
| <b>Startup Exemption for Years of Experience and Turnover</b>                | No                                                                                                                                                                                                                                                               |
| <b>Document required from seller</b>                                         | Certificate (Requested in ATC),Additional Doc 1 (Requested in ATC)<br>*In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer |
| <b>Bid to RA enabled</b>                                                     | No                                                                                                                                                                                                                                                               |
| <b>Primary product category</b>                                              | EXTERNAL MICROMETERS                                                                                                                                                                                                                                             |
| <b>Time allowed for Technical Clarifications during technical evaluation</b> | 5 Days                                                                                                                                                                                                                                                           |
| <b>Estimated Bid Value</b>                                                   | 534086                                                                                                                                                                                                                                                           |
| <b>Evaluation Method</b>                                                     | Item wise evaluation                                                                                                                                                                                                                                             |

### EMD Detail

|          |    |
|----------|----|
| Required | No |
|----------|----|

### ePBG Detail

|          |    |
|----------|----|
| Required | No |
|----------|----|

(a). The EMD % will be applicable for each schedule/group selected during Bid creation.

### Splitting

Bid splitting not applied.

### MII Purchase Preference

|                        |    |
|------------------------|----|
| MI Purchase Preference | No |
|------------------------|----|

Competent Authority Approval for not opting Make In India Preference : [View Document](#)

### MSE Purchase Preference

|                         |     |
|-------------------------|-----|
| MSE Purchase Preference | Yes |
|-------------------------|-----|

1. Purchase preference to Micro and Small Enterprises (MSEs): Purchase preference will be given to MSEs as defined in Public Procurement Policy for Micro and Small Enterprises (MSEs) Order, 2012 dated 23.03.2012 issued by Ministry of Micro, Small and Medium Enterprises and its subsequent Orders/Notifications issued by concerned Ministry. If the bidder wants to avail the Purchase preference, the bidder must be the manufacturer of the offered product in case of bid for supply of goods. Traders are excluded from the purview of Public Procurement Policy for Micro and Small Enterprises. In respect of bid for Services, the bidder must be the Service provider of the offered Service. Relevant documentary evidence in this regard shall be uploaded along with the bid in respect of the offered product or service. If L-1 is not an MSE and MSE Seller (s) has/have quoted price within L-1+ 15% (Selected by Buyer) of margin of purchase preference /price band defined in relevant policy, such Seller shall be given opportunity to match L-1 price and contract will be awarded for 25%(selected by Buyer) percentage of total QUANTITY.

2. Estimated Bid Value indicated above is being declared solely for the purpose of guidance on EMD amount and for determining the Eligibility Criteria related to Turn Over, Past Performance and Project / Past Experience etc. This has no relevance or bearing on the price to be quoted by the bidders and is also not going to have any impact on bid participation. Also this is not going to be used as a criteria in determining reasonableness of quoted prices which would be determined by the buyer based on its own assessment of reasonableness and based on competitive prices received in Bid / RA process.

### Evaluation Method ( Item Wise Evaluation Method )

Contract will be awarded schedulewise and the determination of L1 will be done separately for each schedule. The details of item-consignee combination covered under each schedule are as under:

| Evaluation Schedules | Estimated Value | Item/Category        | Quantity |
|----------------------|-----------------|----------------------|----------|
| Schedule 1           | 19750           | External Micrometers | 2        |
| Schedule 2           | 33982           | External Micrometers | 2        |
| Schedule 3           | 26864           | External Micrometers | 2        |
| Schedule 4           | 49054           | External Micrometers | 2        |
| Schedule 5           | 50000           | External Micrometers | 2        |
| Schedule 6           | 41999           | External Micrometers | 1        |
| Schedule 7           | 45834           | External Micrometers | 1        |

|             |        |                      |    |
|-------------|--------|----------------------|----|
| Schedule 8  | 50975  | Calipers             | 1  |
| Schedule 9  | 119350 | Calipers             | 10 |
| Schedule 10 | 44280  | Calipers             | 5  |
| Schedule 11 | 51998  | External Micrometers | 2  |

## EXTERNAL MICROMETERS ( 2 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

### Technical Specifications

[\\* As per GeM Category Specification](#)

| Specification                             | Specification Name                                                                                                   | Bid Requirement (Allowed Values)                                                                                                                                                      |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPE / MATERIAL                           | <b>Type</b>                                                                                                          | Digital Outside micrometer                                                                                                                                                            |
|                                           | <b>Anvil</b>                                                                                                         | Non-removable anvil with flat measuring face                                                                                                                                          |
|                                           | <b>Shape of the Spindle end</b>                                                                                      | Flat                                                                                                                                                                                  |
|                                           | <b>Spindle end tipped with tungsten carbide</b>                                                                      | No                                                                                                                                                                                    |
| PERFORMANCE                               | <b>Measurement Range (mm)</b>                                                                                        | 0-25                                                                                                                                                                                  |
|                                           | <b>Least Count / Resolution</b>                                                                                      | 0.0001 Or lower                                                                                                                                                                       |
|                                           | <b>Accuracy (Maximum error in reading) at 20 deg C (±)</b>                                                           | 0.0005, 0.001 Or lower                                                                                                                                                                |
| DISPLAY / DATA OUTPUT                     | <b>Type of Display</b>                                                                                               | LCD                                                                                                                                                                                   |
|                                           | <b>Data Output to other devices</b>                                                                                  | No                                                                                                                                                                                    |
| BATTERY                                   | <b>Number of Batteries supplied (Inclusive in the Scope of Supply) (May Indicate '0' for Analog type micrometer)</b> | 1                                                                                                                                                                                     |
| SALIENT FEATURES / FUNCTIONS              | <b>salient Features / Functions</b>                                                                                  | Stem Lock Nut, Spindle Lock, Ratchet drive Thimble, Inch / Metric conversion, Selectable Resolution, Preset Function, Function Lock, Manual ON/OFF, Auto Power OFF, Low battery alarm |
| ACCESSORIES                               | <b>Standard accessories inclusive in the scope of supply</b>                                                         | instruction booklet, Carrying Case                                                                                                                                                    |
| GENERIC                                   | <b>Material of the Frame</b>                                                                                         | Plain Carbon Steel                                                                                                                                                                    |
|                                           | <b>Material of the Spindle and Anvil</b>                                                                             | Hardened Stainless Steel                                                                                                                                                              |
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>                                                                                 | -10 Or lower                                                                                                                                                                          |
|                                           | <b>Maximum Operating Temperature</b>                                                                                 | 60, 70 Or higher                                                                                                                                                                      |

| Specification | Specification Name                                 | Bid Requirement (Allowed Values) |
|---------------|----------------------------------------------------|----------------------------------|
|               | <b>Maximum Operating Humidity at 40 deg C (Rh)</b> | 90, 95 Or higher                 |
| WARRANTY      | <b>Warranty</b>                                    | 1, 2, 3, 5, 8, 10 Or higher      |
| CALIBRATION   | <b>Calibration Certificate issuing authority</b>   | OEM Certificate                  |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepatkata - 786006 Dibrugarh (Assam) | 2        | 60            |

#### EXTERNAL MICROMETERS ( 2 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

#### Technical Specifications

\* [As per GeM Category Specification](#)

| Specification         | Specification Name                                         | Bid Requirement (Allowed Values)             |
|-----------------------|------------------------------------------------------------|----------------------------------------------|
| TYPE / MATERIAL       | <b>Type</b>                                                | Digital Outside micrometer                   |
|                       | <b>Anvil</b>                                               | Non-removable anvil with flat measuring face |
|                       | <b>Shape of the Spindle end</b>                            | Flat                                         |
|                       | <b>Spindle end tipped with tungsten carbide</b>            | No                                           |
| PERFORMANCE           | <b>Measurement Range (mm)</b>                              | 25-50                                        |
|                       | <b>Least Count / Resolution</b>                            | 0.0001, 0.0002, 0.0005, 0.001 Or lower       |
|                       | <b>Accuracy (Maximum error in reading) at 20 deg C (±)</b> | 0.0005, 0.001 Or lower                       |
| DISPLAY / DATA OUTPUT | <b>Type of Display</b>                                     | LCD                                          |
|                       | <b>Data Output to other devices</b>                        | Yes                                          |

| Specification                             | Specification Name                                                                                                   | Bid Requirement (Allowed Values)   |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------|------------------------------------|
| BATTERY                                   | <b>Number of Batteries supplied (Inclusive in the Scope of Supply) (May Indicate '0' for Analog type micrometer)</b> | 1                                  |
| SALIENT FEATURES / FUNCTIONS              | <b>salient Features / Functions</b>                                                                                  | Inch / Metric conversion           |
| ACCESSORIES                               | <b>Standard accessories inclusive in the scope of supply</b>                                                         | instruction booklet, Carrying Case |
| GENERIC                                   | <b>Material of the Frame</b>                                                                                         | Stainless Steel                    |
|                                           | <b>Material of the Spindle and Anvil</b>                                                                             | Hardened Stainless Steel           |
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>                                                                                 | 0, -5, -10 Or lower                |
|                                           | <b>Maximum Operating Temperature</b>                                                                                 | 50, 55, 60, 70 Or higher           |
|                                           | <b>Maximum Operating Humidity at 40 deg C (Rh)</b>                                                                   | 90, 95 Or higher                   |
| WARRANTY                                  | <b>Warranty</b>                                                                                                      | 1, 2, 3, 5, 8, 10 Or higher        |
| CALIBRATION                               | <b>Calibration Certificate issuing authority</b>                                                                     | OEM Certificate                    |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 2        | 60            |

#### EXTERNAL MICROMETERS ( 2 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

#### Technical Specifications

[\\* As per GeM Category Specification](#)

| Specification                             | Specification Name                                                                                                   | Bid Requirement (Allowed Values)                                                                                                                                                                                                                                                                                           |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPE / MATERIAL                           | <b>Type</b>                                                                                                          | Digital Outside micrometer                                                                                                                                                                                                                                                                                                 |
|                                           | <b>Anvil</b>                                                                                                         | Non-removable anvil with flat measuring face                                                                                                                                                                                                                                                                               |
|                                           | <b>Shape of the Spindle end</b>                                                                                      | Flat                                                                                                                                                                                                                                                                                                                       |
|                                           | <b>Spindle end tipped with tungsten carbide</b>                                                                      | No                                                                                                                                                                                                                                                                                                                         |
| PERFORMANCE                               | <b>Measurement Range (mm)</b>                                                                                        | 50-75                                                                                                                                                                                                                                                                                                                      |
|                                           | <b>Least Count / Resolution</b>                                                                                      | 0.0001 Or lower                                                                                                                                                                                                                                                                                                            |
|                                           | <b>Accuracy (Maximum error in reading) at 20 deg C (<math>\pm</math>)</b>                                            | 0.0005, 0.001 Or lower                                                                                                                                                                                                                                                                                                     |
| DISPLAY / DATA OUTPUT                     | <b>Type of Display</b>                                                                                               | LCD                                                                                                                                                                                                                                                                                                                        |
|                                           | <b>Data Output to other devices</b>                                                                                  | Yes                                                                                                                                                                                                                                                                                                                        |
| BATTERY                                   | <b>Number of Batteries supplied (Inclusive in the Scope of Supply) (May Indicate '0' for Analog type micrometer)</b> | 1                                                                                                                                                                                                                                                                                                                          |
| SALIENT FEATURES / FUNCTIONS              | <b>salient Features / Functions</b>                                                                                  | Stem Lock Nut, Spindle Lock, Ratchet drive Thimble, Ratchet drive Speeder, Inch / Metric conversion, Selectable Resolution, Zero-setting, Preset Function, ABSOLUTE Function, Increment Function, Function Lock, Manual ON/OFF, Auto Power OFF, Data Hold, Data Output, Error alarm, Reverse graduation, Low battery alarm |
| ACCESSORIES                               | <b>Standard accessories inclusive in the scope of supply</b>                                                         | Carrying Case                                                                                                                                                                                                                                                                                                              |
| GENERIC                                   | <b>Material of the Frame</b>                                                                                         | Malleable Cast Iron                                                                                                                                                                                                                                                                                                        |
|                                           | <b>Material of the Spindle and Anvil</b>                                                                             | Hardened Stainless Steel                                                                                                                                                                                                                                                                                                   |
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>                                                                                 | 0, -5, -10 Or lower                                                                                                                                                                                                                                                                                                        |
|                                           | <b>Maximum Operating Temperature</b>                                                                                 | 50, 55, 60, 70 Or higher                                                                                                                                                                                                                                                                                                   |
|                                           | <b>Maximum Operating Humidity at 40 deg C (Rh)</b>                                                                   | 70, 75, 80, 85, 90, 95 Or higher                                                                                                                                                                                                                                                                                           |
| WARRANTY                                  | <b>Warranty</b>                                                                                                      | 1, 2, 3, 5, 8, 10 Or higher                                                                                                                                                                                                                                                                                                |
| CALIBRATION                               | <b>Calibration Certificate issuing authority</b>                                                                     | NABL / ILAC accredited agency                                                                                                                                                                                                                                                                                              |

**Consignees/Reporting Officer and Quantity**

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 2        | 60            |

**EXTERNAL MICROMETERS ( 2 pieces )**

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

**Technical Specifications**

\* [As per GeM Category Specification](#)

| Specification                | Specification Name                                                                                            | Bid Requirement (Allowed Values)                                                                                                                                                                                                                          |
|------------------------------|---------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPE / MATERIAL              | Type                                                                                                          | Digital Outside micrometer                                                                                                                                                                                                                                |
|                              | Anvil                                                                                                         | Non-removable anvil with flat measuring face                                                                                                                                                                                                              |
|                              | Shape of the Spindle end                                                                                      | Flat                                                                                                                                                                                                                                                      |
|                              | Spindle end tipped with tungsten carbide                                                                      | Yes                                                                                                                                                                                                                                                       |
| PERFORMANCE                  | Measurement Range (mm)                                                                                        | 75-100                                                                                                                                                                                                                                                    |
|                              | Least Count / Resolution                                                                                      | 0.0001 Or lower                                                                                                                                                                                                                                           |
|                              | Accuracy (Maximum error in reading) at 20 deg C ( $\pm$ )                                                     | 0.0005, 0.001 Or lower                                                                                                                                                                                                                                    |
| DISPLAY / DATA OUTPUT        | Type of Display                                                                                               | LCD                                                                                                                                                                                                                                                       |
|                              | Data Output to other devices                                                                                  | No                                                                                                                                                                                                                                                        |
| BATTERY                      | Number of Batteries supplied (Inclusive in the Scope of Supply) (May Indicate '0' for Analog type micrometer) | 1                                                                                                                                                                                                                                                         |
| SALIENT FEATURES / FUNCTIONS | salient Features / Functions                                                                                  | Stem Lock Nut, Spindle Lock, Ratchet drive Thimble, Ratchet drive Speeder, Inch / Metric conversion, Selectable Resolution, Zero-setting, Preset Function, ABSOLUTE Function, Increment Function, Function Lock, Manual ON/OFF, Auto Power OFF, Data Hold |
| ACCESSORIES                  | Standard accessories inclusive in the scope of supply                                                         | instruction booklet, Carrying Case                                                                                                                                                                                                                        |
| GENERIC                      | Material of the Frame                                                                                         | Stainless Steel                                                                                                                                                                                                                                           |
|                              | Material of the Spindle and Anvil                                                                             | Hardened Stainless Steel                                                                                                                                                                                                                                  |

| Specification                             | Specification Name                                 | Bid Requirement (Allowed Values) |
|-------------------------------------------|----------------------------------------------------|----------------------------------|
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>               | -5, -10 Or lower                 |
|                                           | <b>Maximum Operating Temperature</b>               | 50, 55, 60, 70 Or higher         |
|                                           | <b>Maximum Operating Humidity at 40 deg C (Rh)</b> | 85, 90, 95 Or higher             |
| WARRANTY                                  | <b>Warranty</b>                                    | 1, 2, 3, 5, 8, 10 Or higher      |
| CALIBRATION                               | <b>Calibration Certificate issuing authority</b>   | NABL / ILAC accredited agency    |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 2        | 60            |

#### EXTERNAL MICROMETERS ( 2 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

#### Technical Specifications

[\\* As per GeM Category Specification](#)

| Specification         | Specification Name                                         | Bid Requirement (Allowed Values)             |
|-----------------------|------------------------------------------------------------|----------------------------------------------|
| TYPE / MATERIAL       | <b>Type</b>                                                | Digital Outside micrometer                   |
|                       | <b>Anvil</b>                                               | Non-removable anvil with flat measuring face |
|                       | <b>Shape of the Spindle end</b>                            | Flat                                         |
|                       | <b>Spindle end tipped with tungsten carbide</b>            | Yes                                          |
| PERFORMANCE           | <b>Measurement Range (mm)</b>                              | 125-150                                      |
|                       | <b>Least Count / Resolution</b>                            | 0.0001, 0.0002, 0.0005, 0.001 Or lower       |
|                       | <b>Accuracy (Maximum error in reading) at 20 deg C (±)</b> | 0.0005, 0.001 Or lower                       |
| DISPLAY / DATA OUTPUT | <b>Type of Display</b>                                     | LCD                                          |

| Specification                             | Specification Name                                                                                                   | Bid Requirement (Allowed Values)                                                                                                                                                                                                                                                                                           |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                           | <b>Data Output to other devices</b>                                                                                  | Yes                                                                                                                                                                                                                                                                                                                        |
| BATTERY                                   | <b>Number of Batteries supplied (Inclusive in the Scope of Supply) (May Indicate '0' for Analog type micrometer)</b> | 1                                                                                                                                                                                                                                                                                                                          |
| SALIENT FEATURES / FUNCTIONS              | <b>salient Features / Functions</b>                                                                                  | Stem Lock Nut, Spindle Lock, Ratchet drive Thimble, Ratchet drive Speeder, Inch / Metric conversion, Selectable Resolution, Zero-setting, Preset Function, ABSOLUTE Function, Increment Function, Function Lock, Manual ON/OFF, Auto Power OFF, Data Hold, Data Output, Error alarm, Reverse graduation, Low battery alarm |
| ACCESSORIES                               | <b>Standard accessories inclusive in the scope of supply</b>                                                         | Spanner, Screw Driver, instruction booklet, Carrying Case                                                                                                                                                                                                                                                                  |
| GENERIC                                   | <b>Material of the Frame</b>                                                                                         | Plain Carbon Steel                                                                                                                                                                                                                                                                                                         |
|                                           | <b>Material of the Spindle and Anvil</b>                                                                             | Hardened Stainless Steel                                                                                                                                                                                                                                                                                                   |
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>                                                                                 | -5, -10 Or lower                                                                                                                                                                                                                                                                                                           |
|                                           | <b>Maximum Operating Temperature</b>                                                                                 | 50, 55, 60, 70 Or higher                                                                                                                                                                                                                                                                                                   |
|                                           | <b>Maximum Operating Humidity at 40 deg C (Rh)</b>                                                                   | 80, 85, 90, 95 Or higher                                                                                                                                                                                                                                                                                                   |
| WARRANTY                                  | <b>Warranty</b>                                                                                                      | 1, 2, 3, 5, 8, 10 Or higher                                                                                                                                                                                                                                                                                                |
| CALIBRATION                               | <b>Calibration Certificate issuing authority</b>                                                                     | OEM Certificate                                                                                                                                                                                                                                                                                                            |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 2        | 60            |

#### EXTERNAL MICROMETERS ( 1 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

## Technical Specifications

\* [As per GeM Category Specification](#)

| Specification                             | Specification Name                                                                                                   | Bid Requirement (Allowed Values)                                                                                                                                                                                                         |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPE / MATERIAL                           | <b>Type</b>                                                                                                          | Digital Outside micrometer                                                                                                                                                                                                               |
|                                           | <b>Anvil</b>                                                                                                         | Non-removable anvil with flat measuring face                                                                                                                                                                                             |
|                                           | <b>Shape of the Spindle end</b>                                                                                      | Flat                                                                                                                                                                                                                                     |
|                                           | <b>Spindle end tipped with tungsten carbide</b>                                                                      | Yes                                                                                                                                                                                                                                      |
| PERFORMANCE                               | <b>Measurement Range (mm)</b>                                                                                        | 150-175                                                                                                                                                                                                                                  |
|                                           | <b>Least Count / Resolution</b>                                                                                      | 0.0001 Or lower                                                                                                                                                                                                                          |
|                                           | <b>Accuracy (Maximum error in reading) at 20 deg C (±)</b>                                                           | 0.0005, 0.001 Or lower                                                                                                                                                                                                                   |
| DISPLAY / DATA OUTPUT                     | <b>Type of Display</b>                                                                                               | LCD                                                                                                                                                                                                                                      |
|                                           | <b>Data Output to other devices</b>                                                                                  | Yes                                                                                                                                                                                                                                      |
| BATTERY                                   | <b>Number of Batteries supplied (Inclusive in the Scope of Supply) (May Indicate '0' for Analog type micrometer)</b> | 1                                                                                                                                                                                                                                        |
| SALIENT FEATURES / FUNCTIONS              | <b>salient Features / Functions</b>                                                                                  | Stem Lock Nut, Spindle Lock, Ratchet drive Thimble, Inch / Metric conversion, Selectable Resolution, Zero-setting, Preset Function, ABSOLUTE Function, Increment Function, Function Lock, Auto Power OFF, Data Output, Low battery alarm |
| ACCESSORIES                               | <b>Standard accessories inclusive in the scope of supply</b>                                                         | instruction booklet, Carrying Case                                                                                                                                                                                                       |
| GENERIC                                   | <b>Material of the Frame</b>                                                                                         | Stainless Steel                                                                                                                                                                                                                          |
|                                           | <b>Material of the Spindle and Anvil</b>                                                                             | Hardened Stainless Steel                                                                                                                                                                                                                 |
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>                                                                                 | -5, -10 Or lower                                                                                                                                                                                                                         |
|                                           | <b>Maximum Operating Temperature</b>                                                                                 | 50, 55, 60, 70 Or higher                                                                                                                                                                                                                 |
|                                           | <b>Maximum Operating Humidity at 40 deg C (Rh)</b>                                                                   | 85, 90, 95 Or higher                                                                                                                                                                                                                     |
| WARRANTY                                  | <b>Warranty</b>                                                                                                      | 1, 2, 3, 5, 8, 10 Or higher                                                                                                                                                                                                              |
| CALIBRATION                               | <b>Calibration Certificate issuing authority</b>                                                                     | OEM Certificate                                                                                                                                                                                                                          |

**Consignees/Reporting Officer and Quantity**

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 1        | 60            |

**EXTERNAL MICROMETERS ( 1 pieces )**

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

**Technical Specifications**

[\\* As per GeM Category Specification](#)

| Specification                | Specification Name                                                                                            | Bid Requirement (Allowed Values)                                                                                        |
|------------------------------|---------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| TYPE / MATERIAL              | Type                                                                                                          | Digital Outside micrometer                                                                                              |
|                              | Anvil                                                                                                         | Non-removable anvil with flat measuring face                                                                            |
|                              | Shape of the Spindle end                                                                                      | Flat                                                                                                                    |
|                              | Spindle end tipped with tungsten carbide                                                                      | Yes                                                                                                                     |
| PERFORMANCE                  | Measurement Range (mm)                                                                                        | 175-200                                                                                                                 |
|                              | Least Count / Resolution                                                                                      | 0.0001, 0.0002, 0.0005, 0.001 Or lower                                                                                  |
|                              | Accuracy (Maximum error in reading) at 20 deg C (±)                                                           | 0.0005, 0.001 Or lower                                                                                                  |
| DISPLAY / DATA OUTPUT        | Type of Display                                                                                               | LCD                                                                                                                     |
|                              | Data Output to other devices                                                                                  | Yes                                                                                                                     |
| BATTERY                      | Number of Batteries supplied (Inclusive in the Scope of Supply) (May Indicate '0' for Analog type micrometer) | 1                                                                                                                       |
| SALIENT FEATURES / FUNCTIONS | salient Features / Functions                                                                                  | Stem Lock Nut, Inch / Metric conversion, Zero-setting, ABSOLUTE Function, Manual ON/OFF, Data Output, Low battery alarm |
| ACCESSORIES                  | Standard accessories inclusive in the scope of supply                                                         | Carrying Case                                                                                                           |
| GENERIC                      | Material of the Frame                                                                                         | Malleable Cast Iron                                                                                                     |
|                              | Material of the Spindle and Anvil                                                                             | Hardened Stainless Steel                                                                                                |

| Specification                             | Specification Name                                 | Bid Requirement (Allowed Values) |
|-------------------------------------------|----------------------------------------------------|----------------------------------|
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>               | -5, -10 Or lower                 |
|                                           | <b>Maximum Operating Temperature</b>               | 70 Or higher                     |
|                                           | <b>Maximum Operating Humidity at 40 deg C (Rh)</b> | 75, 80, 85, 90, 95 Or higher     |
| WARRANTY                                  | <b>Warranty</b>                                    | 1, 2, 3, 5, 8, 10 Or higher      |
| CALIBRATION                               | <b>Calibration Certificate issuing authority</b>   | NABL / ILAC accredited agency    |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 1        | 60            |

#### CALIPERS ( 1 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

#### Technical Specifications

[\\* As per GeM Category Specification](#)

| Specification   | Specification Name                                         | Bid Requirement (Allowed Values)                                         |
|-----------------|------------------------------------------------------------|--------------------------------------------------------------------------|
| TYPE / MATERIAL | <b>Caliper Type</b>                                        | Vernier Calipers                                                         |
|                 | <b>Jaw Type</b>                                            | Type A - With jaws on both sides for external and internal measurements. |
|                 | <b>Provided with blade for depth measurement</b>           | Yes                                                                      |
|                 | <b>Provided with Step-Measuring Faces</b>                  | Yes                                                                      |
| PERFORMANCE     | <b>External Measurement Range (mm)</b>                     | 0-1000                                                                   |
|                 | <b>Least Count / Resolution</b>                            | 0.01 Or lower                                                            |
|                 | <b>Accuracy (Maximum error in reading) at 20 deg C (±)</b> | 0.01, 0.015, 0.02, 0.03, 0.04 Or lower                                   |

| Specification                             | Specification Name                                                                                 | Bid Requirement (Allowed Values)                 |
|-------------------------------------------|----------------------------------------------------------------------------------------------------|--------------------------------------------------|
|                                           | <b>Range Per Revolution of the Dial, in case of Dial Caliper (mm)</b>                              | NA for Vernier / Digital type Calipers           |
| DISPLAY / DATA OUTPUT                     | <b>Type of Display</b>                                                                             | Graduated Scale for Vernier / Dial type Calipers |
|                                           | <b>Data Output to other devices</b>                                                                | No                                               |
| BATTERY                                   | <b>Number of Batteries supplied (May Indicate '0' for Vernier / Dial type Calipers )</b>           | 0                                                |
|                                           | <b>Battery Life (Approx) under normal use (May Indicate '0' for Analog type micrometer)"</b>       | 5 Or higher                                      |
| SALIENT FEATURES / FUNCTIONS              | <b>salient Features / Functions</b>                                                                | Locking Screw, Thumb Roller                      |
| ACCESSORIES                               | <b>Standard accessories inclusive in the scope of supply</b>                                       | instruction booklet, Carrying case               |
| GENERIC                                   | <b>Material of the main parts of Callipers such as beam, sliding jaw and depth measuring blade</b> | Hardened Stainless Steel                         |
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>                                                               | 0.0                                              |
|                                           | <b>Maximum Operating Temperature</b>                                                               | 70 Or higher                                     |
|                                           | <b>Maximum Operating Humidity at 40 deg C (Rh)</b>                                                 | 95 Or higher                                     |
| WARRANTY                                  | <b>Warranty</b>                                                                                    | 10 Or higher                                     |
| CALIBRATION                               | <b>Calibration Certificate issuing authority</b>                                                   | OEM Certificate                                  |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 1        | 60            |

## CALIPERS ( 10 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

### Technical Specifications

[\\* As per GeM Category Specification](#)

| Specification                             | Specification Name                                                                                 | Bid Requirement (Allowed Values)                                      |
|-------------------------------------------|----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| TYPE / MATERIAL                           | <b>Caliper Type</b>                                                                                | Digital Calipers                                                      |
|                                           | <b>Jaw Type</b>                                                                                    | Type B - With jaws on one side for external and internal measurements |
|                                           | <b>Provided with blade for depth measurement</b>                                                   | Yes                                                                   |
|                                           | <b>Provided with Step-Measuring Faces</b>                                                          | Yes                                                                   |
| PERFORMANCE                               | <b>External Measurement Range (mm)</b>                                                             | 0-300                                                                 |
|                                           | <b>Least Count / Resolution</b>                                                                    | 0.01 Or lower                                                         |
|                                           | <b>Accuracy (Maximum error in reading) at 20 deg C (±)</b>                                         | 0.01 Or lower                                                         |
|                                           | <b>Range Per Revolution of the Dial, in case of Dial Caliper (mm)</b>                              | 1                                                                     |
| DISPLAY / DATA OUTPUT                     | <b>Type of Display</b>                                                                             | LCD                                                                   |
|                                           | <b>Data Output to other devices</b>                                                                | Yes                                                                   |
| BATTERY                                   | <b>Number of Batteries supplied (May Indicate '0' for Vernier / Dial type Calipers )</b>           | 1                                                                     |
|                                           | <b>Battery Life (Approx) under normal use (May Indicate '0' for Analog type micrometer)"</b>       | 2, 2.5, 3, 3.5, 4, 5 Or higher                                        |
| SALIENT FEATURES / FUNCTIONS              | <b>salient Features / Functions</b>                                                                | Thumb Roller                                                          |
| ACCESSORIES                               | <b>Standard accessories inclusive in the scope of supply</b>                                       | Solar Cell                                                            |
| GENERIC                                   | <b>Material of the main parts of Callipers such as beam, sliding jaw and depth measuring blade</b> | Hardened Stainless Steel                                              |
| OPERATING CONDITIONS / INGRESS PROTECTION | <b>Minimum Operating Temperature</b>                                                               | -10.0                                                                 |
|                                           | <b>Maximum Operating Temperature</b>                                                               | 50, 55, 60, 70 Or higher                                              |

| Specification | Specification Name                                 | Bid Requirement (Allowed Values) |
|---------------|----------------------------------------------------|----------------------------------|
|               | <b>Maximum Operating Humidity at 40 deg C (Rh)</b> | 70, 75, 80, 85, 90, 95 Or higher |
| WARRANTY      | <b>Warranty</b>                                    | 1, 2, 3, 5, 8, 10 Or higher      |
| CALIBRATION   | <b>Calibration Certificate issuing authority</b>   | NABL / ILAC accredited agency    |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 10       | 60            |

#### CALIPERS ( 5 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

#### Technical Specifications

\* [As per GeM Category Specification](#)

| Specification   | Specification Name                                                        | Bid Requirement (Allowed Values)                                      |
|-----------------|---------------------------------------------------------------------------|-----------------------------------------------------------------------|
| TYPE / MATERIAL | <b>Caliper Type</b>                                                       | Digital Calipers                                                      |
|                 | <b>Jaw Type</b>                                                           | Type B - With jaws on one side for external and internal measurements |
|                 | <b>Provided with blade for depth measurement</b>                          | No                                                                    |
|                 | <b>Provided with Step-Measuring Faces</b>                                 | No                                                                    |
| PERFORMANCE     | <b>External Measurement Range (mm)</b>                                    | 0-150                                                                 |
|                 | <b>Least Count / Resolution</b>                                           | 0.01, 0.02 Or lower                                                   |
|                 | <b>Accuracy (Maximum error in reading) at 20 deg C (<math>\pm</math>)</b> | 0.01 Or lower                                                         |
|                 | <b>Range Per Revolution of the Dial, in case of Dial Caliper (mm)</b>     | NA for Vernier / Digital type Calipers                                |

| Specification                             | Specification Name                                                                          | Bid Requirement (Allowed Values)                                                                                                                                                                                                                                                                                                        |
|-------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DISPLAY / DATA OUTPUT                     | Type of Display                                                                             | LCD                                                                                                                                                                                                                                                                                                                                     |
|                                           | Data Output to other devices                                                                | No                                                                                                                                                                                                                                                                                                                                      |
| BATTERY                                   | Number of Batteries supplied (May Indicate '0' for Vernier / Dial type Calipers )           | 1                                                                                                                                                                                                                                                                                                                                       |
|                                           | Battery Life (Approx) under normal use (May Indicate '0' for Analog type micrometer)"       | 1, 2, 2.5, 3, 3.5, 4, 5 Or higher                                                                                                                                                                                                                                                                                                       |
| SALIENT FEATURES / FUNCTIONS              | salient Features / Functions                                                                | Thumb Roller, Ratchet drive Roller, Locking Screw, Inch / Metric conversion, Selectable Resolution, Manual ON/OFF, Auto Power OFF, Zero-setting, Origin-set, Preset Function, Increment Function, Data Hold, Error alarm, Data output; (-) sign, Low battery alarm, counting value composition error alarm, Fine Adjustment Thumb Wheel |
| ACCESSORIES                               | Standard accessories inclusive in the scope of supply                                       | instruction booklet, Carrying case                                                                                                                                                                                                                                                                                                      |
| GENERIC                                   | Material of the main parts of Callipers such as beam, sliding jaw and depth measuring blade | Hardened Stainless Steel                                                                                                                                                                                                                                                                                                                |
| OPERATING CONDITIONS / INGRESS PROTECTION | Minimum Operating Temperature                                                               | -5.0                                                                                                                                                                                                                                                                                                                                    |
|                                           | Maximum Operating Temperature                                                               | 60, 70 Or higher                                                                                                                                                                                                                                                                                                                        |
|                                           | Maximum Operating Humidity at 40 deg C (Rh)                                                 | 90, 95 Or higher                                                                                                                                                                                                                                                                                                                        |
| WARRANTY                                  | Warranty                                                                                    | 1, 2, 3, 5, 8, 10 Or higher                                                                                                                                                                                                                                                                                                             |
| CALIBRATION                               | Calibration Certificate issuing authority                                                   | OEM Certificate                                                                                                                                                                                                                                                                                                                         |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address | Quantity | Delivery Days |
|-------|-----------------------------|---------|----------|---------------|
|-------|-----------------------------|---------|----------|---------------|

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 5        | 60            |

## EXTERNAL MICROMETERS ( 2 pieces )

|            |                  |
|------------|------------------|
| Brand Type | Registered Brand |
|------------|------------------|

### Technical Specifications

[\\* As per GeM Category Specification](#)

| Specification                             | Specification Name                                                                                            | Bid Requirement (Allowed Values)                   |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| TYPE / MATERIAL                           | Type                                                                                                          | Digital Outside micrometer                         |
|                                           | Anvil                                                                                                         | Non-removable anvil with flat measuring face       |
|                                           | Shape of the Spindle end                                                                                      | Flat                                               |
|                                           | Spindle end tipped with tungsten carbide                                                                      | Yes                                                |
| PERFORMANCE                               | Measurement Range (mm)                                                                                        | 100-125                                            |
|                                           | Least Count / Resolution                                                                                      | 0.0001, 0.0002, 0.0005, 0.001 Or lower             |
|                                           | Accuracy (Maximum error in reading) at 20 deg C (±)                                                           | 0.0005, 0.001, 0.002 Or lower                      |
| DISPLAY / DATA OUTPUT                     | Type of Display                                                                                               | LCD                                                |
|                                           | Data Output to other devices                                                                                  | Yes                                                |
| BATTERY                                   | Number of Batteries supplied (Inclusive in the Scope of Supply) (May Indicate '0' for Analog type micrometer) | 1                                                  |
| SALIENT FEATURES / FUNCTIONS              | salient Features / Functions                                                                                  | Function Lock, Ratchet drive Thimble, Zero-setting |
| ACCESSORIES                               | Standard accessories inclusive in the scope of supply                                                         | instruction booklet, Carrying Case                 |
| GENERIC                                   | Material of the Frame                                                                                         | Stainless Steel                                    |
|                                           | Material of the Spindle and Anvil                                                                             | Hardened Stainless Steel                           |
| OPERATING CONDITIONS / INGRESS PROTECTION | Minimum Operating Temperature                                                                                 | 0, -5, -10 Or lower                                |
|                                           | Maximum Operating Temperature                                                                                 | 50, 55, 60, 70 Or higher                           |

| Specification | Specification Name                                 | Bid Requirement (Allowed Values) |
|---------------|----------------------------------------------------|----------------------------------|
|               | <b>Maximum Operating Humidity at 40 deg C (Rh)</b> | 80, 85, 90, 95 Or higher         |
| WARRANTY      | <b>Warranty</b>                                    | 1, 2, 3, 5, 8, 10 Or higher      |
| CALIBRATION   | <b>Calibration Certificate issuing authority</b>   | OEM Certificate                  |

#### Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporting Officer | Address                                                                                                                                              | Quantity | Delivery Days |
|-------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|
| 1     | Dhrupad Rajkhowa            | 786006,M/s Brahmaputra Cracker And Polymer Limited, Contract & Procurement Department, Administrative Building, Lepetkata - 786006 Dibrugarh (Assam) | 2        | 60            |

#### Buyer Added Bid Specific Additional Terms and Conditions

1. Scope of supply (Bid price to include all cost components) : Only supply of Goods
2. Bidders are advised to check applicable GST on their own before quoting. Buyer will not take any responsibility in this regards. GST reimbursement will be as per actuals or as per applicable rates (whichever is lower), subject to the maximum of quoted GST %.
3. Supplier shall ensure that the Invoice is raised in the name of Consignee with GSTIN of Consignee only.
4. While generating invoice in GeM portal, the seller must upload scanned copy of GST invoice and the screenshot of GST portal confirming payment of GST.
5. ISO 9001: The bidder or the OEM of the offered products must have ISO 9001 certification.
6. Buyer Added text based ATC clauses

Bidder to read carefully the technical specification document and SCC document as attached in ATC document. Bidder to submit documents and confirmations as per attached ATC document.

7. Buyer uploaded ATC document [Click here to view the file.](#)

#### Disclaimer

The additional terms and conditions have been incorporated by the Buyer after approval of the Competent Authority in Buyer Organization. Buyer organization is solely responsible for the impact of these clauses on the bidding process, its outcome and consequences thereof including any eccentricity / restriction arising in the bidding process due to these ATCs and due to modification of technical specification and / or terms and conditions governing the bid. Any clause incorporated by the Buyer such as demanding Tender Sample, incorporating any clause against the MSME policy and Preference to make in India Policy, mandating any Brand names or Foreign Certification, changing the default time period for Acceptance of material or payment timeline governed by OM of Department of Expenditure shall be null and void and would not be considered part of bid.

Further any reference of conditions published on any external site or reference to external documents / clauses shall also be null and void. If any seller has any objection / grievance against these additional clauses or otherwise on any aspect of this bid, they can raise their representation against the same by using the Representation window provided in the bid details field in Seller dashboard after logging in as a seller within 4 days of bid publication on GeM. Buyer is duty bound to reply to all such representations and would not be allowed to open bids if he fails to reply to such representations.

[This Bid is also governed by the General Terms and Conditions.](#)

In terms of GeM GTC clause 26 regarding Restrictions on procurement from a bidder of a country which shares a land border with India, any bidder from a country which shares a land border with India will be eligible to bid in this tender only if the bidder is registered with the Competent Authority. While participating in bid, Bidder has to undertake compliance of this and any false declaration and non-compliance of this would be a ground for immediate termination of the contract and further legal action in accordance with the laws.

**---Thank You---**